INFORMATION DISCLOSURE CITATION

(Use several sheets if necessary)

Docket Number (Optional) P206	Application Number UNKNOWN			
Applicant(s) ANNA YEN, ET AL				
Filing Date	Group Art Unit			
UNKNOWN	UKNOWN			

1				UNKNOWN		UKI	NOWIN	1,
				U.S. PATENT DOCUMENTS				
*EXAMINER INITIAL	REF	DOCUMENT NUMBER	DATE	NAME	CLASS	SUBCLASS	FILING DATE IF APPROPRIATE	
		4,357,193	11/2/82	T. W. McGANN, ET AL.	156	286		
		4,944,824	7/31/90	D. GUPTA	156	286		
		5,618,606	4/8/97	G. O. SHERRICK, ET AL.	428	113		
		6,017,484	1/25/2000	H. P. HALE	264	510		
-		WO 01/00405 A2	1/4/2001	XU, GUO, FENG				
				÷				
				·				
	.l	<u> </u>		FOREIGN PATENT DOCUMENTS				
1	REF	DOCUMENT NUMBER	DATE	. COUNTRY	CLASS	SUBCLASS	Translation YES NO	
		, .						
				OTHER DOCUMENTS (Including	Author, Title, 1	Date, Pertinent Pa	iges, Etc.)	
		14 (
EXAMINE	ER			DATE CONSIDERED				
EXAMINE not conside	ER: Init	ial if citation considered, whethe	er or not citation is	in conformance with MPEP Section 609; o applicant.	Draw line thro	igh citation if no	t in conform	ance and

PRIOR ART STATEMENT

1. Patent No: 4,357,193. METHOD OF FABRICATING A COMPOSITE STRUCTURE.

BY McGann, et al.

A vacuum non-autoclave process to de-bulk a lay-up prior to curing is disclosed. The lay-up is placed in a rigid chamber, heated to a temperature wherein the lay-up out gases, while a vacuum is drawn. The patent does not address co-cured honeycomb sandwich with void-free face-sheets.

- 2. Patent No: 4,944,824. PROCESS FOR PREPARATION OF TOOLING OF CARBON FIBER REINFORCED POLYIMIDE FOR COMPOSITE MANUFACTUR by D Gupta. A vacuum is used to draw off volatile components from a lay-up of pre-pregs. The debulking is accomplished in steps. That pre-preg sheets are laid up in stages and debulked. The patent involves high volatile content polyimides and draws off the volatiles rather than minimizing outgassing and uses a subsequent autoclave to cure. It does not address co-cured honeycomb sandwich with void-free face sheets cured without the use of an autoclave.
- 3. Patent No.: 5,618,606. PROCESS FOR BONDING STAGED COMPOSITES WITH A COBONDED STAGED ADHESIVE AND ARTICLE by G. O Sheerrick et al.

 The patent uses vacuum for staging and co-bonding the adhesive and a composite to form a patch, which can be applied to a damaged substrate for repair. It does not address co-cured honeycomb sandwich with void-free face sheets.
- 4. Patent No.: 6,017,484. METHOD FOR MANUFACTURE OF MINIMUM POROSITY, WRINKLE FREE COMPOSITE PARTS by H. P. Hale

The patent applies to thermoplastic rather than thermoset composites. It uses a stepped two-chamber pressure reduction rather than constant full vacuum with a single vacuum bag. It does not address co-cured honeycomb sandwich with void-free face sheets.

5. Patent No.: WO 01/00405 A2. MANUFACTURE OF VOID FREE LAMINATES AND USE THEREOF by Xu et al.

The invention uses partially impregnated unidirectional prepreg tapes to produce void-free laminates under vacuum only cures. It references sandwich on p 14, Para 5-10 and honeycomb core in p 59, Para 63. The patent does not use a separate adhesive layer or layers to form honeycomb sandwich structure. The subject invention uses a multi-step cure to stabilize the adhesive before curing the prepreg.

Respectfully submitted;

Louis L. Dachs

Reg. No.: 26,858

Attorney for Applicants/Assignee

Dec 12, 2003